

ITEM NO.
CONVECTION STEAMER
22CET6
ONE (1) REQUIRED

- A. Furnish one (1) each electric, boilerless, one compartment, convection steamer model number 22CET6 as specified as manufactured by Cleveland. Total exterior perimeter dimensions to be sized properly in order that unit fits in available space.
- B. Provide 14-gauge stainless steel construction for compartment doors, cavities and steam generator. Provide unit with 4" skid resistant adjustable legs with flanged feet.
- C. Provide steamer door with heavy duty, two-piece, solid compartment design with free-floating inner door with reversible door gasket.
- D. Provide fan forced convection steam with **KleanShield** cooking compartment design. **KleanShield** collects and removes condensate waste from the cooking compartment keeping the compartment clean, safe from impurities and easy to maintain, eliminates foaming and avoids contamination of the reservoir water.
- E. Automatic water level control fills when main power switch is turned on, low water and high water probes inside cooking compartment maintains water levels during cooking, eliminating the need to manually refill and monitor water level during cooking.
- F. The timer automatically adjusts the cooking time with the volume of product being cooked, eliminating guesswork on when the product is finished. Includes a 60-minute electro-mechanical timer, LED indicator lights for **SureCook** cycle, power on and reset. Provide timed and manual bypass switch for constant steaming.
- G. Provide additional safety overflow standpipe, 193° preheat and standby temperature, high temperature safety shut-off and steam and fan shut off control when the door is opened.
- H. Electric heating elements are installed within aluminum blocks for fast and efficient heat transfer. Elements never need deliming because they are not immersed in water.
- I. Unit will accept up to six (6) each 2 ½" deep steam pans.
- J. Voltage to be _____, 60 Hz, three phase.
- K. Provide the unit with the following accessories:

34" High Stainless Steel Stand

- L. Units shall comply with UL and UL Sanitation Standards.
- M. Provide manufacturer's (2) year parts and labor warranty.
- N. Unit to be delivered, uncrated, and set in place. All packing materials to be removed from job site.