

**ITEM NO.**  
**CONVECTION STEAMER**  
**24CGA10**  
**ONE (1) REQUIRED**

- A. Furnish one (1) each gas, two compartment, convection steamer model number 24CGA10 as specified as manufactured by Cleveland. Total exterior perimeter dimensions to be sized properly in order that unit fits in available space.
- B. Provide 14-gauge stainless steel construction for compartment doors, cavities and steam generator. Provide 6" stainless steel legs with adjustable flanged feet for a one-inch level adjustment.
- C. Provide steamer doors with heavy duty, two-piece, solid compartment design with free-floating inner door with reversible door gasket.
- D. Solid-state controls operate water level and safety functions.
- E. Unique patented steam cooking distribution system produces high velocity convection steam without fans. Coved corner design in cooking compartments distributes heat evenly and is easy to keep clean. Creased bottom enhances drainage. Cold water condenser maintains a dry steam. Provide fully insulated cooking compartment with removable stainless steel slide racks for easy cleaning.
- F. High efficiency gas, vertical atmospheric steam generator is rated at 125,000 BTU is 80% efficient and only uses 75,000 BTU when one compartment is used. Unit shall be provided with electronic spark ignition and automatic water fill on startup. Unit shall be provided with automatic generator drain at shutdown featuring a water jet spray rinse cleaning cycle to keep drain clear. Provide automatic water level control system with low water power cutoff circuit.
- G. Provide easy access cleaning port and indicator light to advise the operator that it is time to delime the generator.
- H. Provide instant steam standby mode.
- I. Unit will accept up to five (5) each 2 1/2" deep steam pans per compartment.
- J. Unit to be designed for \_\_\_\_\_ gas. Control voltage is 115/60/1.
- K. Provide the unit with the following accessories:

Kleensteam® AR-X Water Filter

- L. Unit shall be UL, AGA, NSF, ASME, CSA, CGA and ETL approved.
- M. Provide manufacturer's two (2) year parts and labor warranty.
- N. Unit to be delivered, uncrated, and set in place. All packing materials to be removed from job site.