

ITEM NO.
PRESSURELESS STEAMER - ELECTRIC
36-CEM-16-48
ONE (1) REQUIRED

- A. Furnish one (1) each electric, two compartment, pressureless steamer, model number 36-CEM-16-48 as manufactured by Cleveland. .
- B. Each compartment shall be equipped with a 60-minute timer, separate bypass switch for constant steaming and a cold water condenser for superior cooking results. All controls shall be serviceable from the front.
- C. Provide with instant stand by mode to hold generator at steaming temperature and allow unit to start cooking instantly.
- D. Electric steam generator is rated at 48 KW and is **coated with NickelGuard™** and is provided with a **5-year pro-rated boiler warranty**. Unit shall be provided with automatic water fill on startup. Unit shall be provided with automatic generator drain at shutdown featuring a water jet spray rinse cleaning cycle to keep drain clear. Provide automatic water level control system with low water power cutoff circuit. Steam generator provided with high limit pressure safety switch, 15-psi safety valve.
- E. Unit shall have type 304 stainless steel cooking compartment and NSF certified 6” stainless steel legs with adjustable flanged feet for a one-inch level adjustment.
- F. Unit shall have unique patented steam cooking system, which allows the patented convection jets to produce a high velocity convection steam without fans. Coved corners design in cooking compartment to distribute heat evenly and allow easy cleaning. Creased bottom to enhance drainage. Cold water condenser for each compartment to maintain a dry steam. Fully insulated cooking compartment for thermal efficiency. Removable stainless steel slide racks for easy cleaning.
- G. Provide with heavy duty, one piece, solid compartment door design with replaceable door gasket.
- H. Doors to be hinged left with controls on right.
- I. Provide with heavy-duty stainless steel base frame.
- J. Unit will accept up to eight (8) each 2 ½” deep steam pans per compartment.
- K. Electrical requirements shall be: _____.
- L. Provide the unit with the following accessories:

Secondary Low Water Cut-Off
Timer with Compensating Load Feature
Boiler Descaling Pump Kit

- M. Unit shall be UL, NSF, ASME, CSA, and ETL approved.
- N. Provide manufacturer's (2) year parts and labor warranty and 5-year pro-rated boiler warranty.
- O. Unit to be delivered, uncrated, and set in place. All packing materials to be removed from job site.