

**ITEM NO.**  
**CONVECTION STEAMER**  
**36CGM16300**  
**( ) REQUIRED**

- A. Furnish \_\_\_\_\_ (\_\_\_) gas, two compartment, convection steamer model number 36CGM16300 as specified as manufactured by Cleveland. Total exterior perimeter dimensions to be sized properly in order that unit fits in available space.
- B. Provide modular stainless steel cabinet base with hinged door. Steam cooking cavities and compartment doors shall be 10-gauge stainless steel construction. Provide heavy-duty stainless steel base frame and 6" stainless steel legs with adjustable flanged feet for a one-inch level adjustment.
- C. Provide steamer doors with heavy duty, one piece, solid compartment design with replaceable door gaskets.
- D. Solid-state controls operate water level and safety functions.
- E. Unique patented steam cooking distribution system produces high velocity convection steam without fans. Coved corner design in cooking compartments distributes heat evenly and is easy to keep clean. Creased bottom enhances drainage. Cold water condenser maintains a dry steam. Provide fully insulated cooking compartment with removable stainless steel slide racks for easy cleaning.
- F. High efficiency gas steam generator is rated at 300,000 BTU and is **coated with NickelGuard™** and is provided with a **5-year pro-rated boiler warranty**. Unit shall be provided with electronic spark ignition and automatic water fill on startup. Unit shall be provided with automatic generator drain at shutdown featuring a water jet spray rinse cleaning cycle to keep drain clear. Provide automatic water level control system with low water power cutoff circuit. Steam generator is equipped with high limit pressure safety switch, 15-psi safety valve.
- G. Provide instant steam standby mode.
- H. Unit will accept up to eight (8) each 2 ½" deep steam pans per compartment.
- I. Unit to be designed for \_\_\_\_\_ gas. Control voltage is 115/60/1.
- J. Provide the unit with the following accessories:

Secondary Low Water Cut-Off  
Boiler Descaling Pump Kit  
Timer with Compensating Load Feature  
Rear Gas Connection

- K. Unit shall be UL, AGA, NSF, ASME, CSA, CGA and ETL approved.
- L. Provide manufacturer's (2) year parts and labor warranty and 5-year pro-rated boiler warranty.
- M. Unit to be delivered, uncrated, and set in place. All packing materials to be removed from job site.