

Choice

Equipment Company

The Right Choice is Yours!

**Food
Service
Equipment**



**5974 Highway 129, Unit L
Pendergrass, GA 30567
(706) 693-2484 Office
(706) 693-2468 Fax
www.choiceequipmentcompany.com**

Terms & Conditions:

- All Prices are F.O.B. factory, Pendergrass, Ga.
- All terms are shown US Dollars.
- Terms: Net 30 days to trade of established credit only unless otherwise stated for established accounts. without notice. All prices, specifications and discounts are subject to change. The manufacturer reserves the right to make changes in design or material when deemed necessary.
- All orders can be submitted via e-mail or fax and are subject to acceptance by the factory.
- All merchandise leaves factory in first class condition. Delivery to the carrier relieves us of further responsibility. For damages or loss while in transit, file claim against carrier promptly. Notify factory immediately if shortages occur within five (5) days from the date the merchandise is received.
- Any applicable federal, state, or local sales tax will be added to the price.
- No part of this catalog may be reproduced in any manner without written permission from Choice Equipment Company, Inc.
- We will not break cartons, where applicable.

Quotations and Customs

- Quotations are valid for 30 days, unless otherwise stated.
- Custom drawings for custom fabrication product must be signed and will be accepted as correct. Any errors arising from the same will be the responsibility of the customer.
- Made to order items are not returnable. Special fabricated items are not subject to return or cancellation under any circumstances.

Returns

- Do not return equipment without written authorization. All requests for eligible returns must be made within 30 days of our invoice date.
- Contact the factory for written approval to return merchandise.
- Returned goods must be received within 30 days of written return authorization.
- Returned merchandise must be returned in the original, unopened and resalable packaging or properly packed to prevent damage in transit.
- Returned goods authorization number will be assigned to merchandise to assure proper credit and must be noted on the shipping label and bill of lading.
- On return shipment, where orders have been correctly filled out and are not defective, a 25% handling charge will be applied. All incoming freight or express charges must be prepaid.
- Certain products, such as made to order are not returnable. Contact Customer Service for the policy concerning specific products.

Cancellations

- Cancellations are not accepted on orders in transit or on custom equipment in production.

Freight Terms and Conditions

- Freight, service and handling charges are not subject to discount.
- Freight carriers will be chosen by the factory unless Purchase Order specifies customer carrier and includes Prepaid & Add with third party billing address.
- Choice Equipment will use all reasonable commercial efforts to maintain the shipping date acknowledged or quoted by the Seller.
- Choice Equipment is not responsible for any delays in delivery which are beyond our control such as flood, strikes, fires, natural disasters delays, in transportation or any contingencies of similar character.
- Freight claims for damages are the responsibility of the customer and all claims must be filed by the customer with the carrier promptly.
- Choice Equipment freight classes are based on descriptions and generalizations provided by the National Motor Freight Traffic Association, January 2007 catalog. These classes are subject to interpretation by the shipper and carrier.
- Those items with the symbol (SPD) can be shipped via a small package delivery service.

Special Handling Charges

- Customers will be billed for trucking company charges that are due to special requests made by the customer, including: Notifying a customer before making a delivery, Requiring a lift gate truck, Making deliveries during special hours.

Credit and Collection

- No merchandise will be shipped to an account which is not current.
- Past due account are subject to 1-1/2% late fee on all balances past due.
- If it is necessary to turn over an account for collection, all charges incurred in doing so will be added to the total amount due.

Warranty

- Choice Equipment Company warrants its equipment to be free from defect as a result of materials or workmanship for a period of 2 years. Wheels and casters are warranted for a period of 1 year by the manufacture.
- Any changes or alterations of original equipment or parts thereof void the warranty. Improper installation or abuse of equipment such as: overloading shelving units, wet applications for dry equipment; where by employee misuse of product will void warranty. Please use equipment for intended purposes.
- Claims must be mailed to in writing to: Choice Equipment Company, Inc., 5974 US Hwy. 129 N., Pendergrass, GA. 30567
- Choice Equipment Company reserves the right to replace or repair said item upon inspection. Transportation charges may apply.
- Aluminum equipment is warranted to not rust for the life of the product. (Casters and fastening devices excluded)

Table of Contents

Pan Racks

Page 1

Shelving Units

Page 19

Can Racks

Page 33

Rack Covers

Page 37

Cabinets

Page 39

Utility Carts

Page 43

PR SERIES PAN RACKS

**Aluminum and
Stainless Steel**

PR 10 sheet pan racks 18x26, half size, knock-downpgs. 2 & 3 & 4

PR 15 nesting sheet pan rackspg. 5

PR 17 insert rackspg. 6

PR 18 tray retrieval rackspg. 6

PR 20 universal angle pan racks 18x26, 12x20pg. 7

PR 25 oval tray rackspg. 7

PR 30 steam table pan racks 12x20pg. 8

PR 35 platter racks 10x30, 12x30pg. 9

PR 40 lug rackspg. 9

PR 45 bulk moverspg. 10

PR 50 ingredient binspg. 11

PR 55 poly food box rackspg. 11

PR 58 glass rackspg. 12

PR 60 channel pan rackspg. 12

PR 70 universal shelf cartspg. 11

PR 80 oven racks 18x26pgs. 14, 15, 16 & 17

SHEET PAN racks for 18x26 trays

All welded construction, 1-1/8" Alum. Sq. Tube, .078 aluminum angles, 1" Sq. SS Tube
6063-aluminum alloy, 16 ga. Type 304 stainless, 5" poly-u swivel casters.

END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR10-A-1820	21	533	26	660	69	1,753	20	3	76	46	21
PR10-A-1818/65	21	533	26	660	64	1,626	18	3	76	45	20
PR10-A-1815	21	533	26	660	69	1,753	15	4	102	40	18
PR10-A-1812	21	533	26	660	69	1,753	12	5	127	38	17
PR10-A-1810	21	533	26	660	69	1,753	10	6	152	36	16



Freight Class: 300



END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR10-S-1820	21	533	26	660	69	1,753	20	3	76	92	42
PR10-S-1818/65	21	533	26	660	64	1,626	18	3	76	89	40
PR10-S-1815	21	533	26	660	69	1,753	15	4	102	86	39
PR10-S-1812	21	533	26	660	69	1,753	12	5	127	83	38
PR10-S-1810	21	533	26	660	69	1,753	10	6	152	81	37



Freight Class: 300



SHEET PAN racks for 18x26 trays

All welded construction, 1-1/8" Alum. Sq. Tube, .078 aluminum angles, 1" Sq. SS Tube
6063-aluminum alloy, 16 ga. Type 304 stainless, 5" poly-u swivel casters.

SIDE LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR10-A-2620	28	711	18	457	69	1,753	20	3	76	42	19
PR10-A-2618/65	28	711	18	457	64	1,626	18	3	76	41	19
PR10-A-2615	28	711	18	457	69	1,753	15	4	102	36	16
PR10-A-2612	28	711	18	457	69	1,753	12	5	127	34	15
PR10-A-2610	28	711	18	457	69	1,753	10	6	152	32	15



Freight Class: 300



SIDE LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR10-S-2620	28	711	18	457	69	1,753	20	3	76	90	41
PR10-S-2618/65	28	711	18	457	64	1,626	18	3	76	87	39
PR10-S-2615	28	711	18	457	69	1,753	15	4	102	84	38
PR10-S-2612	28	711	18	457	69	1,753	12	5	127	81	37
PR10-S-2610	28	711	18	457	69	1,753	10	6	152	79	36



Freight Class: 300



STANDARD 1/2 SIZE SHEET PAN RACKS

All welded construction, 1-1/8" Alum. Sq. Tube, .078 aluminum angles, 1" Sq. SS Tube
6063-aluminum alloy, 16 ga. Type 304 stainless, 5" poly-u swivel casters.

END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR10-A-186H	21	533	26	660	38	965	6	5	127	30	14
PR10-A-1810H	21	533	26	660	38	965	10	3	76	35	16



Freight Class: 300



END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR10-S-186H	21	533	26	660	38	965	6	5	127	55	25
PR10-S-1810H	21	533	26	660	38	965	10	3	76	59	27



Freight Class: 300



KNOCK-DOWN SHEET PAN RACKS

Knock-down pan racks for 18x26 trays
1" square construction, 1"x 1-1/2" angle, 5" TPR stem casters

END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR10-A-1820-KD	21	533	26	660	69	1,753	20	3	76	38	17
PR10-A-1818-65-KD	21	533	26	660	64	1,626	18	3	76	36	16
PR10-A-1812-KD	21	533	26	660	69	1,753	12	5	127	32	15

Freight Class: 70

NESTING PAN RACK

All welded construction, 1-1/8" Alum. Sq. Tube, .078 aluminum angles, 1" Sq. SS Tube
6063-aluminum alloy, 16 ga. Type 304 stainless, 5" poly-u swivel casters.

END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR15-A-1820-N	23	584	26	660	69	1,753	20	3	76	46	21
PR15-A-1818/65-N	23	584	26	660	64	1,626	18	3	76	45	20
PR15-A-1815-N	23	584	26	660	69	1,753	15	4	102	40	18
PR15-A-1812-N	23	584	26	660	69	1,753	12	5	127	38	17
PR15-A-1810-N	23	584	26	660	69	1,753	10	6	152	36	16

Freight Class: 300

END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR15-S-1820-N	23	584	26	660	69	1,753	20	3	76	92	42
PR15-S-1818/65-N	23	584	26	660	64	1,626	18	3	76	89	40
PR15-S-1815-N	23	584	26	660	69	1,753	15	4	102	86	39
PR15-S-1812-N	23	584	26	660	69	1,753	12	5	127	83	38
PR15-S-1810-N	23	584	26	660	69	1,753	10	6	152	81	37

Freight Class: 300

CONTACT FACTORY FOR MORE INFORMATION

INSERT RACKS

All welded 6063 aluminum construction, 1" square tubing, 1"x1-1/2" .078 angles,

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR17-A-718	21	533	24	610	23	584	7	3	76	15	7
PR17-A-1618	21	533	24	610	51	1,295	16	3	76	27	12



Freight Class: 300



TRAY RETRIEVAL RACKS 30" deep

All welded construction, 1-1/8" square tubing, 1"x1-1/2" .078 aluminum angles, 6063-aluminum alloy, 5" poly-u swivel casters.

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
For 14" x 18" trays											
PR18-A-1812/30	21	533	24	610	51	1,295	16	3	76	27	12
For 15" x 20" trays											
PR18-A-2012/30	21	533	24	610	51	1,295	16	3	76	27	12



Freight Class: 300



UNIVERSAL ANGLE PAN RACKS FOR 18X26 TRAYS AND 12X20 STEAM TABLE PANS

Heavy-duty all-welded construction, 1-1/8" square tubing, 1"x 3-1/4"x .090 alum. angles, 6063-aluminum alloy, 5" poly-u swivel casters.

END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)		(in)	(mm)	(lb)	(kg)
PR20-A-1820	22	559	26	660	69	1,753	20	3	76	96	44
PR20-A-1818/65	22	559	26	660	64	1,626	18	3	76	94	43
PR20-A-1815	22	559	26	660	69	1,753	15	4	102	91	41
PR20-A-1812	22	559	26	660	69	1,753	12	5	127	85	39
PR20-A-1811/65	22	559	26	660	64	1,626	11	5	127	83	38



Freight Class: 300



OVAL TRAY RACKS

FOR 18X26 TRAYS, 12X20 STEAM TABLE PANS,
LARGE OVAL TRAYS

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)		(in)	(mm)	(lb)	(kg)
PR25-A-2320	26	660	26	660	69	1,753	20	3	76	105	48
PR25-A-2318/65	26	660	26	660	64	1,626	18	3	76	103	47
PR25-A-2315	26	660	26	660	69	1,753	15	4	102	92	42
PR25-A-2312	26	660	26	660	69	1,753	12	5	127	84	38
PR25-A-2310	26	660	26	660	69	1,753	10	6	152	80	36



Freight Class: 300

Heavy-duty all-welded construction, 1-1/4" square tubing,
1-1/4"x 6-1/4" .100 alum. angles,
6063-aluminum alloy, 5" poly-u swivel casters.



STEAM TABLE PAN RACKS FOR 12X20 PANS

All welded construction, 1-1/8" Alum. Sq. Tube, .078 aluminum angles
6063-aluminum alloy, 5" poly-u swivel casters.

END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(12x20)	(in)	(mm)	(lb)	(kg)
PR30-A-15	17	432	26	660	69	1,753	15	4	102	30	14
PR30-A-20	17	432	26	660	69	1,753	20	3	76	34	15
PR30-A-10/38	17	432	26	660	38	965	10	3	76	25	11



Freight Class: 300



SIDE LOAD (DOUBLE-DEEP)

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(12x20)	(in)	(mm)	(lb)	(kg)
PR30-A-24	24	610	26	660	69	1,753	24	5	127	31	14
PR30-A-40	24	610	26	660	69	1,753	40	3	76	41	19



Freight Class: 300

PLATTER RACKS FOR 10X30 AND 12X30 TRAYS

All welded construction, 1-1/8" Alum. Sq. Tube, .078 aluminum angles
6063-aluminum alloy, 5" poly-u swivel casters.

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)					
For 10" x 30" platters											
PR35-A-1010	13	330	26	660	69	1,753	10	6	152	30	14
PR35-A-1012	13	330	26	660	69	1,753	12	5	127	32	15
For 12" x 30" platters											
PR35-A-1210	15	381	26	660	69	1,753	10	6	152	30	14
PR35-A-1212	15	381	26	660	69	1,753	12	5	127	33	15



Freight Class: 300



Pan Racks

LUG RACKS FOR PLASTIC 7" AND 8" LUGS (SOLD SEPARATELY)

All welded construction, 1-1/8" Alum. Sq. Tube, .078 aluminum angles
6063-aluminum alloy, 5" poly-u swivel casters.

Model Number	Overall Dimensions						Lug Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINIUM	(in)	(mm)	(in)	(mm)	(in)	(mm)					
PR40-A-1	16	406	26	660	19	483	1			11	5
PR40-A-2	16	406	26	660	34	864	2	18	457	19	9
PR40-A-3	19	483	26	660	41	1,041	3	10	254	25	11
PR40-A-4	19	483	26	660	54	1,372	4	10	254	29	13
PR40-A-6	19	483	26	660	69	1,753	6	9	229	31	14



Freight Class: 300

OPTION
H - HANDLE



BULK MOVERS WITH BUSHEL TUB

**All welded construction, 1-1/8" Alum. Sq. Tube, .078 aluminum angles
6063-aluminum alloy, 5" poly-u swivel casters.**

Model Number	Overall Dimensions						Tub Cap.	Approx Ship Wt	
	Width		Length		Height			(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)		
PR45-A-3	22	559	30	762	32	813	3 bushel	46	24
PR45-A-6	22	559	36	914	36	914	6 bushel	45	33
PR45-A-8	22	559	40	1016	36	914	8 bushel	40	41

Freight Class: 300



Model Number	Overall Dimensions						Tub Cap.	Approx Ship Wt	
	Width		Length		Height			(lb)	(kg)
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)			
PR45-S-3	22	559	30	762	32	813	3 bushel	92	33
PR45-S-6	22	559	36	914	36	914	6 bushel	89	42
PR45-S-8	22	559	40	1016	36	914	8 bushel	86	49

Freight Class: 300



INGREDIENT BIN RACKS

WITH HEAVY DUTY POLYETHYLENE BINS AND LIDS

Available in white, blue, and yellow

All welded construction, 1" square tubing, 1"x1-1/2"
6063-aluminum alloy, 5" poly-u swivel casters.

Model Number	Overall Dimensions						Bin Cap.	Approx Ship Wt	
	Width		Length		Height			(lb)	(kg)
ALUMINIUM	(in)	(mm)	(in)	(mm)	(in)	(mm)			
PR50-A-2	20	508	17	432	30	762	2	25	11
PR50-A-3	29	737	17	432	30	762	3	36	16
Replacement bins/lids									
50-A-BIN	20	508	17	432				5	2
50-A-LID	29	737	17	432				2	1

Freight Class: 250



POLY FOOD BOX RACKS

All welded construction, 1-1/8" square tubing, 1-1/2" channels, hold tub by the lip
6063-aluminum alloy, 5" poly-u swivel casters.

Model Number	Overall Dimensions						Bin Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINIUM	(in)	(mm)	(in)	(mm)	(in)	(mm)					
PR55-A-8	21	533	26	660	69	1,753	8	6	152	32	15
PR55-A-15	21	533	26	660	69	1,753	15	4	102	37	17
PR55-A-20	21	533	26	660	69	1,753	20	3	76	43	20
PR55-A-5/38	21	533	26	660	38	965	5	6	152	27	12



Freight Class: 300



GLASS TRAY RACKS

All welded construction, 1-1/8" square tubing, 1"x1-1/2" x.078 angle
6063-aluminum alloy, 5" poly-u swivel casters.

Model Number	Overall Dimensions						Tray Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)		(in)	(mm)	(lb)	(kg)
PR58-A-620	23	584	20	508	69	1,753	6	9	229	27	12
PR58-A-820	23	584	20	508	69	1,753	8	7	178	29	13



Freight Class: 300



CHANNEL PAN RACKS FOR 18X26 TRAYS

All welded construction, 1-1/8" square tubing, 1-1/2" channel,
6063-aluminum alloy, 5" poly-u swivel casters.

END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR60-A-1820/38	21	533	26	660	38	965	20	1.5	38	32	15
PR60-A-1840	21	533	26	660	69	1,753	40	1.5	38	43	20



Freight Class: 300

SIDE LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR60-A-2640	28	711	18	457	69	1,753	40	1.5	38	43	20



Freight Class: 300



UNIVERSAL SHELF CARTS

All welded construction, $\frac{1}{2}$ " & 1-1/8" square tubing, 1-1/2" channel, 6063-aluminum alloy, 5" poly-u swivel casters.

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINIUM	(in)	(mm)	(in)	(mm)	(in)	(mm)					
For 18" x 26" trays											
PR70-A-4-T-43	21	533	26	660	43	1,092	4	10	254	26	12
PR70-A-5-T-43	21	533	26	660	43	1,092	5	7	178	30	14
PR70-A-5-T	21	533	26	660	69	1,753	5	12	305	32	15
PR70-A-6-T	21	533	26	660	69	1,753	6	11	279	36	16
PR70-A-7-T	21	533	26	660	69	1,753	7	9	229	40	18
PR70-A-8-T	21	533	26	660	69	1,753	8	7	178	45	20
For 10" & 12" x 30"											
PR70-A-4-P-43	16	406	32	813	43	1,092	4	10	254	25	11
PR70-A-5-P	16	406	32	813	69	1,753	5	12	305	30	14
PR70-A-8-P *	16	406	32	813	69	1,753	8	7	178	42	19



Freight Class: 300



PAN RACK OPTIONS: (all welded units, only)

- 520U 5x2 Poly-U Caster upgrade
- BK Locking Brakes (2)
- VB Vertical Bumpers (4)
- B Corner Bumpers (with plate casters or solid base)
- SB Solid Base
- SBCB Solid Base with full perimeter bumper
- TGA Tray Guard for aluminum racks
- TGS Tray Guard for stainless steel racks
- AT Aluminum Top
- ST Stainless Top
- PT Poly Top

OVEN RACKS

When ordering your oven rack:

In order for us to satisfy your needs, the more information we have about your oven the better we can make sure you receive the correct style of rack. Please supply the oven model number, serial number (if available), and the size of the oven (one rack or two rack capacity) when ordering your oven racks.

LIFT STYLES:



Ordering Info

Add to model number ...

then add the lift style

AD Adamatic
BA Bakers-Aid
BX Baxter
HO Hobart
LA Lang
LK Lucks
RV Revent

A A-lift
B B-lift
C C-lift
PIN for Bakers-Aid
bottom carousel oven

example: PR80-A-2612-HO-C

(aluminum, side load, 12-runner, C-lift, for a Hobart oven)

Option: TG

tray guard

REPLACEMENT OVEN WHEELS:

Model # 4HTP

OVEN RACKS FOR 18 X 26 TRAYS

For Adamatic, Bakers-Aid, Baxter, Hobart, Lang, Lucks, and Revent ovens

All welded construction, 1-1/8" Alum. Sq. Tube, .078 aluminum angles, 1" Sq. SS Tube
6063-aluminum alloy, 16 ga. Type 304 stainless, 4"Hi-Temp Phenolic swivel plate casters.

END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR80-A-1820	21	533	26	660	As Req'd		20	3	76	46	21
PR80-A-1815	21	533	26	660	As Req'd		15	4	102	40	18
PR80-A-1812	21	533	26	660	As Req'd		12	5	127	38	17
PR80-A-1810	21	533	26	660	As Req'd		10	6	152	36	16



Freight Class: 300



END LOAD

Model Number	Overall Dimensions						Pan Cap.	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(in)	(mm)	(lb)	(kg)
PR80-S-1820	21	533	26	660	As Req'd		20	3	76	92	42
PR80-S-1815	21	533	26	660	As Req'd		15	4	102	86	39
PR80-S-1812	21	533	26	660	As Req'd		12	5	127	83	38
PR80-S-1810	21	533	26	660	As Req'd		10	6	152	81	37



Freight Class: 300



OVEN RACKS

SIDE LOAD

Model Number	Overall Dimensions						Pan Cap. (18x26)	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)					
PR80-A-2620	28	711	18	457	As Req'd		20	3	76	42	19
PR80-A-2615	28	711	18	457	As Req'd		15	4	102	36	16
PR80-A-2612	28	711	18	457	As Req'd		12	5	127	34	15
PR80-A-2610	28	711	18	457	As Req'd		10	6	152	32	15



Freight Class: 300



SIDE LOAD

Model Number	Overall Dimensions						Pan Cap. (18x26)	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
STAINLESS	(in)	(mm)	(in)	(mm)	(in)	(mm)					
PR80-S-2620	28	711	18	457	As Req'd		20	3	76	90	41
PR80-S-2615	28	711	18	457	As Req'd		15	4	102	84	38
PR80-S-2612	28	711	18	457	As Req'd		12	5	127	81	37
PR80-S-2610	28	711	18	457	As Req'd		10	6	152	79	36



Freight Class: 300



OVEN RACKS

HOLDS TWO 18 X 26 TRAYS PER SHELF

SIDE LOAD DOUBLE DEEP

Model Number	Overall Dimensions						Pan Cap. (18x26)	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)		(in)	(mm)	(lb)	(kg)
PR80-A-2620-D	28	711	36	914	As Req'd		20	3	76	54	24
PR80-A-2615-D	28	711	36	914	As Req'd		15	4	102	48	22
PR80-A-2612-D	28	711	36	914	As Req'd		12	5	127	40	18
PR80-A-2610-D	28	711	36	914	As Req'd		10	6	152	38	17



NOTE: FOR DOUBLE RACK OVENS ONLY



HOLDS TWO 18 X 26 TRAYS PER SHELF

SIDE LOAD DOUBLE DEEP

Model Number	Overall Dimensions						Pan Cap. (18x26)	Runner Spacing		Approx Ship Wt	
	Width		Length		Height			(in)	(mm)	(lb)	(kg)
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)		(in)	(mm)	(lb)	(kg)
PR80-S-2620-D	28	711	36	914	As Req'd		20	3	76	115	52
PR80-S-2615-D	28	711	36	914	As Req'd		15	4	102	96	44
PR80-S-2612-D	28	711	36	914	As Req'd		12	5	127	92	42
PR80-S-2610-D	28	711	36	914	As Req'd		10	6	152	84	38



NOTE: FOR DOUBLE RACK OVENS ONLY

SU SERIES SHELVING UNITS

Aluminum

SU 10 fixed shelving units, tubular, channel, t-bar, solidpg. 20

SU 15 mobile fixed shelving units, tubular, channel, t-bar, solidpg. 21

SU 20 adjustable shelving units, tubular, channel, t-bar, solidpg. 22

SU 30 dunnage racks, tubular, channel,pg. 23-24

SU 35 mobile dunnage racks, tubular, channelpg. 25

SU 40 adjustable keg rackspg. 26-27

SU 45 fixed keg rackspg. 26

SU 50 fixed tray drying rackspg. 28

SU 55 adjustable tray drying rackspg. 28

SU 60 fixed cantilever shelving units, tubular, channel, t-bar, solidpg. 29

SU 70 boat rackspg. 30

SU 90 wall shelves, tubular, channel, t-bar, solidpg. 31

FIXED SHELVING UNITS

20" & 24" DEEP, 2-3-4 SHELF UNITS

All welded construction, 1-1/2" square tubing, 6063-aluminum alloy
1500 lb. capacity per shelf

Model Number				Overall Dimensions						Approx Ship Wt	
2-SHELF UNITS				Length		Depth		Height			
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU10-3620-2-T	SU10-3620-2-C	SU10-3620-2-TB	SU10-3620-2-S	36	914	20	508	60	1524	28	13
SU10-3624-2-T	SU10-3624-2-C	SU10-3624-2-TB	SU10-3624-2-S	36	914	24	610	60	1524	30	14
SU10-4820-2-T	SU10-4820-2-C	SU10-4820-2-TB	SU10-4820-2-S	48	1219	20	508	60	1524	33	15
SU10-4824-2-T	SU10-4824-2-C	SU10-4824-2-TB	SU10-4824-2-S	48	1219	24	610	60	1524	37	17
SU10-6020-2-T	SU10-6020-2-C	SU10-6020-2-TB	SU10-6020-2-S	60	1524	20	508	60	1524	38	17
SU10-6024-2-T	SU10-6024-2-C	SU10-6024-2-TB	SU10-6024-2-S	60	1524	24	610	60	1524	43	20



Freight Class: 300



Model Number				Overall Dimensions						Approx Ship Wt	
3-SHELF UNITS				Length		Depth		Height			
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU10-3620-3-T	SU10-3620-3-C	SU10-3620-3-TB	SU10-3620-3-S	36	914	20	508	60	1524	38	17
SU10-3624-3-T	SU10-3624-3-C	SU10-3624-3-TB	SU10-3624-3-S	36	914	24	610	60	1524	42	19
SU10-4820-3-T	SU10-4820-3-C	SU10-4820-3-TB	SU10-4820-3-S	48	1219	20	508	60	1524	46	21
SU10-4824-3-T	SU10-4824-3-C	SU10-4824-3-TB	SU10-4824-3-S	48	1219	24	610	60	1524	51	23
SU10-6020-3-T	SU10-6020-3-C	SU10-6020-3-TB	SU10-6020-3-S	60	1524	20	508	60	1524	54	24
SU10-6024-3-T	SU10-6024-3-C	SU10-6024-3-TB	SU10-6024-3-S	60	1524	24	610	60	1524	61	28



Freight Class: 300

Model Number				Overall Dimensions						Approx Ship Wt	
4-SHELF UNITS				Length		Depth		Height			
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU10-3620-4-T	SU10-3620-4-C	SU10-3620-4-TB	SU10-3620-4-S	36	914	20	508	72	1829	48	22
SU10-3624-4-T	SU10-3624-4-C	SU10-3624-4-TB	SU10-3624-4-S	36	914	24	610	72	1829	54	24
SU10-4820-4-T	SU10-4820-4-C	SU10-4820-4-TB	SU10-4820-4-S	48	1219	20	508	72	1829	59	27
SU10-4824-4-T	SU10-4824-4-C	SU10-4824-4-TB	SU10-4824-4-S	48	1219	24	610	72	1829	66	30
SU10-6020-4-T	SU10-6020-4-C	SU10-6020-4-TB	SU10-6020-4-S	60	1524	20	508	72	1829	70	32
SU10-6024-4-T	SU10-6024-4-C	SU10-6024-4-TB	SU10-6024-4-S	60	1524	24	610	72	1829	79	36



Freight Class: 300

MOBILE FIXED SHELVING UNITS

20" & 24" DEEP, 2-3-4 SHELF UNITS

All welded construction, 1-1/2" square tubing, 6063-aluminum alloy.
Mounted on heavy duty wheel channel with HD 6x2 Poly-O casters

Model Number				Overall Dimensions						Approx Ship Wt	
2-SHELF UNITS				Length		Depth		Height		Ship Wt	
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU15-3620-2-T	SU15-3620-2-C	SU15-3620-2-TB	SU15-3620-2-S	36	914	20	508	60	1524	38	17
SU15-3624-2-T	SU15-3624-2-C	SU15-3624-2-TB	SU15-3624-2-S	36	914	24	610	60	1524	40	18
SU15-4820-2-T	SU15-4820-2-C	SU15-4820-2-TB	SU15-4820-2-S	48	1219	20	508	60	1524	43	20
SU15-4824-2-T	SU15-4824-2-C	SU15-4824-2-TB	SU15-4824-2-S	48	1219	24	610	60	1524	47	21
SU15-6020-2-T	SU15-6020-2-C	SU15-6020-2-TB	SU15-6020-2-S	60	1524	20	508	60	1524	48	22
SU15-6024-2-T	SU15-6024-2-C	SU15-6024-2-TB	SU15-6024-2-S	60	1524	24	610	60	1524	53	24



Freight Class: 300



Model Number				Overall Dimensions						Approx Ship Wt	
3-SHELF UNITS				Length		Depth		Height		Ship Wt	
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU15-3620-3-T	SU15-3620-3-C	SU15-3620-3-TB	SU15-3620-3-S	36	914	20	508	60	1524	48	22
SU15-3624-3-T	SU15-3624-3-C	SU15-3624-3-TB	SU15-3624-3-S	36	914	24	610	60	1524	52	24
SU15-4820-3-T	SU15-4820-3-C	SU15-4820-3-TB	SU15-4820-3-S	48	1219	20	508	60	1524	56	25
SU15-4824-3-T	SU15-4824-3-C	SU15-4824-3-TB	SU15-4824-3-S	48	1219	24	610	60	1524	61	28
SU15-6020-3-T	SU15-6020-3-C	SU15-6020-3-TB	SU15-6020-3-S	60	1524	20	508	60	1524	64	29
SU15-6024-3-T	SU15-6024-3-C	SU15-6024-3-TB	SU15-6024-3-S	60	1524	24	610	60	1524	71	32



Freight Class: 300

Model Number				Overall Dimensions						Approx Ship Wt	
4-SHELF UNITS				Length		Depth		Height		Ship Wt	
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU15-3620-4-T	SU15-3620-4-C	SU15-3620-4-TB	SU15-3620-4-S	36	914	20	508	72	1829	58	26
SU15-3624-4-T	SU15-3624-4-C	SU15-3624-4-TB	SU15-3624-4-S	36	914	24	610	72	1829	64	29
SU15-4820-4-T	SU15-4820-4-C	SU15-4820-4-TB	SU15-4820-4-S	48	1219	20	508	72	1829	69	31
SU15-4824-4-T	SU15-4824-4-C	SU15-4824-4-TB	SU15-4824-4-S	48	1219	24	610	72	1829	76	34
SU15-6020-4-T	SU15-6020-4-C	SU15-6020-4-TB	SU15-6020-4-S	60	1524	20	508	72	1829	80	36
SU15-6024-4-T	SU15-6024-4-C	SU15-6024-4-TB	SU15-6024-4-S	60	1524	24	610	72	1829	89	40



Freight Class: 300

ADJUSTABLE SHELVING

18", 20" & 24" DEEP

Heavy Duty 1-1/2" x 1-3/4" tubing, 4"E-channel, 1-1/2" T-bar, .063 sheet, 6063-aluminum alloy
Corner block construction with SS set screw

Model Number				Overall Dimensions				Approx Ship Wt	
				Length		Depth		(lb)	(kg)
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU20-3618-T	SU20-3618-C	SU20-3618-TB	SU20-3618-S	36	914	18	457	10	5
SU20-3620-T	SU20-3620-C	SU20-3620-TB	SU20-3620-S	36	914	20	508	13	6
SU20-3624-T	SU20-3624-C	SU20-3624-TB	SU20-3624-S	36	914	24	610	15	7
SU20-4818-T	SU20-4818-C	SU20-4818-TB	SU20-4818-S	48	1219	18	457	12	5
SU20-4820-T	SU20-4820-C	SU20-4820-TB	SU20-4820-S	48	1219	20	508	15	7
SU20-4824-T	SU20-4824-C	SU20-4824-TB	SU20-4824-S	48	1219	24	610	17	8
SU20-6018-T	SU20-6018-C	SU20-6018-TB	SU20-6018-S	60	1524	18	457	14	6
SU20-6020-T	SU20-6020-C	SU20-6020-TB	SU20-6020-S	60	1524	20	508	17	8
SU20-6024-T	SU20-6024-C	SU20-6024-TB	SU20-6024-S	60	1524	24	610	19	9



Freight Class: 70

ADJUSTABLE SHELVING OPTIONS

Model Number	Overall Dimensions		Approx Ship Wt	
	Length			
Posts	Length		Approx Ship Wt	
SU20-AP12	12"	305	1	0
SU20-AP24	24"	610	2	1
SU20-AP36	36"	914	2	1
SU20-AP48	48"	1219	3	1
SU20-AP54	54"	1372	3	1
SU20-AP68	68"	1727	4	2
SU20-AP76	76"	1930	4	2
SU20-AP84	84"	2134	5	2



Model Number	Overall Dimensions				Approx Ship Wt	
	Length		Depth			
U-Braces	Length		Depth		Approx Ship Wt	
SU20-UB3618	36	914	18	457	3	1
SU20-UB4818	48	1219	18	457	3	1
SU20-UB6018	60	1524	18	457	4	2
SU20-UB3620	36	914	20	508	4	2
SU20-UB4820	48	1219	20	508	5	2
SU20-UB6020	60	1524	20	508	5	2
SU20-UB3624	36	914	24	610	5	2
SU20-UB4824	48	1219	24	610	6	3
SU20-UB6024	60	1524	24	610	6	3



Freight Class: 70

DUNNAGE RACKS

Tubular (T) Channel (C), 20" & 24" deep, 8" & 12" legs,
**TUBULAR – All welded construction, 1-1/2" square tubing,
 6063-aluminum alloy, plastic caps on legs**

Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
3' TUBULAR	(in)	(mm)	(in)	(mm)	(in)	(mm)	Pounds	(lb)	(kg)
SU30-36208-T	36	914	20	508	8	203	3000	10	5
SU30-362012-T	36	914	20	508	12	305	3000	11	5
SU30-36248-T	36	914	24	610	8	203	3000	12	5
SU30-362412-T	36	914	24	610	12	305	3000	13	6



Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
4' TUBULAR	(in)	(mm)	(in)	(mm)	(in)	(mm)	Pounds	(lb)	(kg)
SU30-48208-T	48	1219	20	508	8	203	2500	12	5
SU30-482012-T	48	1219	20	508	12	305	2500	13	6
SU30-48248-T	48	1219	24	610	8	203	2500	14	6
SU30-482412-T	48	1219	24	610	12	305	2500	15	7



Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
5' TUBULAR	(in)	(mm)	(in)	(mm)	(in)	(mm)	Pounds	(lb)	(kg)
SU30-60208-T	60	1524	20	508	8	203	2200	16	7
SU30-602012-T	60	1524	20	508	12	305	2200	17	8
SU30-60248-T	60	1524	24	610	8	203	2200	18	8
SU30-602412-T	60	1524	24	610	12	305	2200	20	9



DUNNAGE RACKS

Tubular (T) Channel (C), 20" & 24" deep, 8" & 12" legs,
CHANNEL – All welded construction

1-1/2" square tubing, 4" E-channel 6063-aluminum alloy, plastic caps on legs

Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
3' CHANNEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	Pounds	(lb)	(kg)
SU30-36208-C	36	914	20	508	8	203	3000	11	5
SU30-362012-C	36	914	20	508	12	305	3000	12	5
SU30-36248-C	36	914	24	610	8	203	3000	13	6
SU30-362412-C	36	914	24	610	12	305	3000	14	6



Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
4' CHANNEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	Pounds	(lb)	(kg)
SU30-48208-C	48	1219	20	508	8	203	2500	13	6
SU30-482012-C	48	1219	20	508	12	305	2500	14	6
SU30-48248-C	48	1219	24	610	8	203	2500	15	7
SU30-482412-C	48	1219	24	610	12	305	2500	16	7



Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
5' CHANNEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	Pounds	(lb)	(kg)
SU30-60208-C	60	1524	20	508	8	203	2200	17	8
SU30-602012-C	60	1524	20	508	12	305	2200	18	8
SU30-60248-C	60	1524	24	610	8	203	2200	19	9
SU30-602412-C	60	1524	24	610	12	305	2200	21	10



MOBILE DUNNAGE RACKS

20" & 24" DEEP

6x2 Poly-O swivel casters, 2 swivel w/brakes, 2 rigid
 1-1/2" square tubing, 4" E-channel
 6063-aluminum alloy • 2000 lb. rolling capacity

Model Number	Overall Dimensions						Pan Cap.	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
3' CHANNEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	Pounds	(lb)	(kg)
SU35-3620	36	914	20	508	10	254	2000	23	10
SU35-3624	36	914	24	610	10	254	2000	25	11



Freight Class: 70



Model Number	Overall Dimensions						Pan Cap.	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
4' CHANNEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	Pounds	(lb)	(kg)
SU35-4820	48	1219	20	508	10	254	2000	25	11
SU35-4824	48	1219	24	610	10	254	2000	27	12



Freight Class: 70

Model Number	Overall Dimensions						Pan Cap.	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
5' CHANNEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	Pounds	(lb)	(kg)
SU35-6020	60	1524	20	508	10	254	2000	29	13
SU35-6024	60	1524	24	610	10	254	2000	31	14



Freight Class: 70

ADJUSTABLE KEG STORAGE RACKS

Top shelf is tubular, bottom two shelves are aluminum channel construction.

1-1/2" x 2" tubular shelf design with round adjustable posts.

6063-aluminum alloy, plastic caps on posts

Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Width		Length		Height			(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	Kegs		
SU40-4	42	1067	18	457	76	1930	4	47	21
SU40-6	60	1524	18	457	76	1930	6	53	24
SU40-8	80	2032	18	457	76	1930	8	62	28
SU40-10 *	93	2362	18	457	76	1930	10	78	35



Freight Class: 70

* comes with 2 extra round center poles and clips



FIXED KEG STORAGE RACKS

Top shelf is tubular, bottom two shelves are channel construction.

1-1/2" x 2" tubular shelf design

Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Length		Depth		Height			(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	Kegs		
SU45-4	42	1067	18	457	76	1930	4	49	22
SU45-6	60	1524	18	457	76	1930	6	55	25
SU45-8	80	2032	18	457	76	1930	8	65	29
SU45-10	93	2362	18	457	76	1930	10	81	37



Freight Class: 70



ADJUSTABLE KEG RACK OPTIONS

KEG RACK SHELVES

Model Number	Overall Dimensions				For Model	Approx Ship Wt	
	Length		Depth			(lb)	(kg)
Top Tubular	(in)	(mm)	(in)	(mm)			
SU40-T4	42	1067	18	457	SU40-4	12	5
SU40-T6	60	1524	18	457	SU40-6	14	6
SU40-T8	80	2032	18	457	SU40-8	16	7
SU40-T10	93	2362	18	457	SU40-10	18	8



Freight Class: 70

Model Number	Overall Dimensions				For Model	Approx Ship Wt	
	Length		Depth			(lb)	(kg)
Bottom Channel	(in)	(mm)	(in)	(mm)			
SU40-B4	42	1067	18	457	SU40-4	16	7
SU40-B6	60	1524	18	457	SU40-6	19	9
SU40-B8	80	2032	18	457	SU40-8	21	10
SU40-B10	93	2362	18	457	SU40-10	23	10



Freight Class: 70

KEG RACK OPTIONS

Model Number	Overall Dimensions				For Model	Approx Ship Wt	
	Length		Depth			(lb)	(kg)
U-Braces	(in)	(mm)	(in)	(mm)			
SU40-U4	42	1067	18	457	SU40-4	3	1
SU40-U6	60	1524	18	457	SU40-6	5	2
SU40-U8	80	2032	18	457	SU40-8	7	3
SU40-U10	93	2362	18	457	SU40-10	8	4



Freight Class: 70

Model Number	Overall Dimensions				For Model	Approx Ship Wt	
	Height					(lb)	(kg)
Posts	(in)	(mm)					
SU40-SP76	76	1930			All	4	2
SU40-10-CLIP					SU40-10	1	1



Freight Class: 70

FIXED TRAY DRYING STORAGE RACKS

Two, three, and four shelf capacity

Mobile on 6x2 Poly-O casters, available in 1", 1-1/2", and 3" spacing, heavy-duty all welded construction, 6063 aluminum alloy

Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Length		Depth		Height			Shelves	(lb)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)			
SU50-2	60	1524	28	711	as req'd		2	175	79
SU50-3	60	1524	28	711	as req'd		3	200	91
SU50-4	60	1524	28	711	as req'd		4	225	102



Freight Class: 400

Notice: ALL fixed racks require a sample tray with order



ADJUSTABLE TRAY DRYING STORAGE RACKS

Two, three, and four shelf capacity

Mobile on 6x2 Poly-O casters, available in 1", 1-1/2", and 3" spacing, heavy-duty all welded shelf construction, 6063 aluminum alloy

Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Length		Depth		Height			Shelves	(lb)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)			
SU55-2	60	1524	28	711	76	1930	2	170	77
SU55-3	60	1524	28	711	76	1930	3	195	88
SU55-4	60	1524	28	711	76	1930	4	215	98



Freight Class: 400



FIXED CANTILEVER SHELVING UNITS

20" & 24" DEEP, 2-3-4 SHELF UNITS

All welded construction, 2"x4" tubular uprights, 6063-aluminum alloy,
front adjustable feet, removable bottom shelf

Model Number				Overall Dimensions						Approx Ship Wt	
2-SHELF UNITS				Length		Depth		Height		(lb)	(kg)
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(in)	(mm)		
SU60-3620-2-T	SU60-3620-2-C	SU60-3620-2-TB	SU60-3620-2-S	36	914	20	508	72	1829	50	23
SU60-3624-2-T	SU60-3624-2-C	SU60-3624-2-TB	SU60-3624-2-S	36	914	24	610	72	1829	56	25
SU60-4820-2-T	SU60-4820-2-C	SU60-4820-2-TB	SU60-4820-2-S	48	1219	20	508	72	1829	56	25
SU60-4824-2-T	SU60-4824-2-C	SU60-4824-2-TB	SU60-4824-2-S	48	1219	24	610	72	1829	60	27
SU60-6020-2-T	SU60-6020-2-C	SU60-6020-2-TB	SU60-6020-2-S	60	1524	20	508	72	1829	66	30
SU60-6024-2-T	SU60-6024-2-C	SU60-6024-2-TB	SU60-6024-2-S	60	1524	24	610	72	1829	66	30



Freight Class: 300

Model Number				Overall Dimensions						Approx Ship Wt	
3-SHELF UNITS				Length		Depth		Height		(lb)	(kg)
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(in)	(mm)		
SU60-3620-3-T	SU60-3620-3-C	SU60-3620-3-TB	SU60-3620-3-S	36	914	20	508	72	1829	56	25
SU60-3624-3-T	SU60-3624-3-C	SU60-3624-3-TB	SU60-3624-3-S	36	914	24	610	72	1829	65	29
SU60-4820-3-T	SU60-4820-3-C	SU60-4820-3-TB	SU60-4820-3-S	48	1219	20	508	72	1829	70	32
SU60-4824-3-T	SU60-4824-3-C	SU60-4824-3-TB	SU60-4824-3-S	48	1219	24	610	72	1829	76	34
SU60-6020-3-T	SU60-6020-3-C	SU60-6020-3-TB	SU60-6020-3-S	60	1524	20	508	72	1829	80	36
SU60-6024-3-T	SU60-6024-3-C	SU60-6024-3-TB	SU60-6024-3-S	60	1524	24	610	72	1829	87	39



Freight Class: 400



Model Number				Overall Dimensions						Approx Ship Wt	
4-SHELF UNITS				Length		Depth		Height		(lb)	(kg)
Tubular	Channel	T-Bar	Solid	(in)	(mm)	(in)	(mm)	(in)	(mm)		
SU60-3620-4-T	SU60-3620-4-C	SU60-3620-4-TB	SU60-3620-4-S	36	914	20	508	72	1829	69	31
SU60-3624-4-T	SU60-3624-4-C	SU60-3624-4-TB	SU60-3624-4-S	36	914	24	610	72	1829	73	33
SU60-4820-4-T	SU60-4820-4-C	SU60-4820-4-TB	SU60-4820-4-S	48	1219	20	508	72	1829	85	39
SU60-4824-4-T	SU60-4824-4-C	SU60-4824-4-TB	SU60-4824-4-S	48	1219	24	610	72	1829	93	42
SU60-6020-4-T	SU60-6020-4-C	SU60-6020-4-TB	SU60-6020-4-S	60	1524	20	508	72	1829	98	44
SU60-6024-4-T	SU60-6024-4-C	SU60-6024-4-TB	SU60-6024-4-S	60	1524	24	610	72	1829	107	49



Freight Class: 400

ALUMINUM BOAT RACKS

ALL WELDED CHANNEL AND TUBULAR CONSTRUCTION

6063-aluminum alloy

Available in both table mount and wall mount designs

Model Number	Overall Dimensions						Approx Ship Wt	
	Length		Depth		Height			
WALL MOUNT	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU70-36-W	36	914	15	381	20	508	15	7
SU70-48-W	48	1219	15	381	20	508	17	8
SU70-60-W	60	1524	15	381	20	508	20	9
SU70-72-W	72	1829	15	381	20	508	23	10

NSF Freight Class: 250



Model Number	Overall Dimensions						Approx Ship Wt	
	Length		Depth		Height			
TABLE MOUNT	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU70-36-T	36	914	15	381	20	508	15	7
SU70-48-T	48	1219	15	381	20	508	17	8
SU70-60-T	60	1524	15	381	20	508	20	9
SU70-72-T	72	1829	15	381	20	508	23	10

NSF Freight Class: 250

WALL SHELVES

AVAILABLE IN CHANNEL AND SOLID TOP DESIGNS. 12" & 18" DEPTHS

All welded aluminum construction, 6063-aluminum alloy
(Mounting hardware not included)

Model Number	Overall Dimensions				Approx Ship Wt	
	Width		Length			
CHANNEL	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU90-3612-C	36	914	12	305	7	3
SU90-3618-C	36	914	18	457	13	6
SU90-4812-C	48	1219	12	305	8	4
SU90-4818-C	48	1219	18	457	16	7
SU90-6012-C	60	1524	12	305	9	4
SU90-6018-C	60	1524	18	457	19	9



Freight Class: 70



Model Number	Overall Dimensions				Approx Ship Wt	
	Width		Length			
SOLID	(in)	(mm)	(in)	(mm)	(lb)	(kg)
SU90-3612-S	36	914	12	305	7	3
SU90-3618-S	36	914	18	457	13	6
SU90-4812-S	48	1219	12	305	8	4
SU90-4818-S	48	1219	18	457	16	7
SU90-6012-S	60	1524	12	305	9	4
SU90-6018-S	60	1524	18	457	19	9



Freight Class: 70



CR SERIES CAN RACKS

Aluminum

CR 162 standard can rack, stationary, 162-can capacity	pg. 34
CR 162M standard can rack, mobile, 162-can capacity	pg. 34
CR 216 standard can rack, stationary, 216-can capacity	pg. 34
CR 156-FF First-In, First-out can rack, stationary, 156-can capacity	pg. 34
CRE 162 economy can rack, stationary, 162-can capacity	pg. 34
CR 54 1/2-size can rack, mobile, 54-can capacity, open top	pg. 35
CR 54-A 1/2-size can rack, mobile, 54-can capacity, aluminum top	pg. 35
CR 54-PT 1/2-size can rack, mobile, 54-can capacity, poly top	pg. 35
CR 54-SS 1/2-size can rack, mobile, 54-can capacity, stainless top	pg. 35
CR 72 1/2-size can rack, mobile, 72-can capacity, open top	pg. 35
CR 72-A 1/2-size can rack, mobile, 72-can capacity, aluminum top	pg. 35
CR 72-PT 1/2-size can rack, mobile, 72-can capacity, poly top	pg. 35
CR 72-SS 1/2-size can rack, mobile, 72-can capacity, stainless top	pg. 35

CAN RACKS ALUMINUM

**Full Size, Standard, Mobile, First In-First Out, Economy,
All Mobile on 5" Poly-U Casters**

Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Width		Depth		Height			(lb)	(kg)
FULL SIZE-STANDARD	(in)	(mm)	(in)	(mm)	(in)	(mm)	#10 Cans	(lb)	(kg)
CR162	35	889	25	635	72	1829	162	62	28
CR162M *	36	914	28	711	78	1981	162	74	34
CR216	35	889	37	940	72	1829	216	89	40



Freight Class: 400

* Mobile Unit, 5" Poly-U Casters



Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Width		Depth		Height			(lb)	(kg)
First In - First Out	(in)	(mm)	(in)	(mm)	(in)	(mm)	#10 Cans	(lb)	(kg)
CR156-FF	42	1067	28	711	80	2032	156	205	93



Freight Class: 400

Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Width		Depth		Height			(lb)	(kg)
Economy	(in)	(mm)	(in)	(mm)	(in)	(mm)	#10 Cans	(lb)	(kg)
CRE162	35	889	25	635	72	1829	162	52	24



Freight Class: 400



CAN RACKS ALUMINUM

1/2-Size Units with optional tops 1/2-Size – Can Racks – All Mobile on 5" Poly-U Casters

Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Width		Depth		Height			(lb)	(kg)
1/2 SIZE - MOBILE, 35"	(in)	(mm)	(in)	(mm)	(in)	(mm)	#10 Cans	(lb)	(kg)
CR54 (open top)	35	889	28	711	35	889	54	48	22
CR54-A (aluminum top)	35	889	28	711	35	889	54	55	25
CR54-PT (poly top)	35	889	28	711	35	889	54	64	29
CR54-SS (stainless top)	35	889	28	711	35	889	54	65	29



Freight Class: 400



Model Number	Overall Dimensions						Capacity	Approx Ship Wt	
	Width		Depth		Height			(lb)	(kg)
1/2 SIZE - MOBILE, 42"	(in)	(mm)	(in)	(mm)	(in)	(mm)	#10 Cans	(lb)	(kg)
CR72 (open top)	35	889	28	711	42	1067	72	50	23
CR72-A (aluminum top)	35	889	28	711	42	1067	72	67	30
CR72-PT (poly top)	35	889	28	711	42	1067	72	75	34
CR72-SS (stainless top)	35	889	28	711	42	1067	72	77	35



Freight Class: 250

RTC SERIES RACK COVERS

Aluminum

RTC 69 rack cover for standard tall end-load rack	pg. 38
RTC 65 rack cover for 64" tall end-load rack	pg. 38
RTC 38 rack cover for 38" tall end-load rack	pg. 38
FRTC 69 Freezer rack cover for standard tall end-load rack	pg. 38
FRTC 65 Freezer rack cover for 64" tall end-load rack	pg. 38
FRTC 38 Freezer rack cover for 38" tall end-load rack	pg. 38

STANDARD RACK COVERS FOR STANDARD PAN RACKS

**12 ga vinyl, reinforced top, 2-full zippers,
High Quality – Flexible to zero degrees**

Model Number	Overall Dimensions						Approx Ship Wt	
	Width		Length		Height		(lb)	(kg)
	(in)	(mm)	(in)	(mm)	(in)	(mm)		
RTC69	23	584	28	711	64	1,626	5	2
RTC65	23	584	28	711	60	1,524	5	2
RTC38	23	584	28	711	33	838	4	2



FREEZER RACK COVERS FOR STANDARD PAN RACKS

Model Number	Overall Dimensions						Approx Ship Wt	
	Width		Length		Height		(lb)	(kg)
	(in)	(mm)	(in)	(mm)	(in)	(mm)		
FRTC69	23	584	28	711	64	1,626	6	3
FRTC65	23	584	28	711	60	1,524	6	3
FRTC38	23	584	28	711	33	838	5	2

Custom Sizes Available upon Request
All covers ship via UPS

CC SERIES CABINETS

Aluminum

CC16 Aluminum Enclosed Cabinet, 32" Tallpg. 40

CC24 Aluminum Enclosed Cabinet, 44" Tallpg. 40

CC32 Aluminum Enclosed Cabinet, End Load, 56" Tallpg. 40

CC40 Aluminum Enclosed Cabinet, End Load, 40-Tray Capacitypg. 40

CC60 Aluminum Enclosed Cabinet, End Load, 60-Tray Capacitypg. 40

CCSR16 Aluminum 1-1/2" Spacing, 16-Tray Capacitypg. 41

CCSR32 Aluminum 1-1/2" Spacing, 32-Tray Capacitypg. 41

CCSR40 Aluminum 1-1/2" Spacing, 40-Tray Capacitypg. 41

CCSR60 Aluminum 1" Spacing, 60-Tray Capacitypg. 41

CABINETS

Enclosed, Aluminum Construction, Stainless Hardware
 Designed For 18x26 Trays, Available in 1" and 1-1/2" spacing,
 Full Size Mobile units on 5" Poly-U Casters, all swivel, front 2 w/brakes,
 Door swings open 270 degrees with gravity latch

Model Number	Overall Dimensions						Pan Cap.	Approx Ship Wt	
	Width		Depth		Height			(18x26)	(lb)
END LOAD, 1-1/2" SPACING	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(lb)	(kg)
CC40	23	584	28	711	70	1778	40	108	49
CC32	23	584	28	711	56	1422	32	98	44
CC24	23	584	28	711	44	1118	24	90	41
CC16	23	584	28	711	32	813	16	82	37



Freight Class: 400



Model Number	Overall Dimensions						Pan Cap.	Approx Ship Wt	
	Width		Depth		Height			(18x26)	(lb)
END LOAD, 1" SPACING	(in)	(mm)	(in)	(mm)	(in)	(mm)	(18x26)	(lb)	(kg)
CC60	23	584	28	711	70	1778	60	115	52



Freight Class: 400

SOLID SIDE – “SPEED” RACKS

Open Front and Back, Solid Top & Bottom
 Designed For 18x26 Trays, Available in 1" and 1-1/2" spacing,
 5" Poly-U Plate Casters, all swivel, front 2 w/brakes

Model Number	Overall Dimensions						Pan Cap. (18x26)	Approx Ship Wt	
	Width		Depth		Height			(lb)	(kg)
END LOAD, 1-1/2" SPACING	(in)	(mm)	(in)	(mm)	(in)	(mm)			
CCSR40	23	584	28	711	70	1778	40	88	40
CCSR32	23	584	28	711	56	1422	32	78	35
CCSR16	23	584	28	711	32	813	16	68	31

Freight Class: 300



Model Number	Overall Dimensions						Pan Cap. (18x26)	Approx Ship Wt	
	Width		Depth		Height			(lb)	(kg)
END LOAD, 1" SPACING	(in)	(mm)	(in)	(mm)	(in)	(mm)			
CCSR60	23	584	28	711	70	1778	60	95	43

Freight Class: 300

UC SERIES UTILITY CARTS

Aluminum, Steel
and Stainless Steel

- UC 10 aluminum utility carts, 2 & 3 shelf cartspg. 44
- UC 20 stainless steel utility carts, 2 & 3 shelf cartspg. 44
- UC 30 aluminum transport cart, channel constructionpg. 45
- UC 40 steel tubular deck cartpg. 45
- UC 50 produce carts, galvanized steelpg. 46
- UC 60 produce cart with reversible top, galvanized steelpg. 46
- UC 70 aluminum Queen Mary carts, 2,3,4,5 & 6 shelf unitspg. 47
- UC 80 stainless steel Queen Mary carts, 2,3,4,5 & 6 shelf unitspg. 47-48
- UC 100 aluminum dolliespg. 48
- UC 130 aluminum sheet pan dolliespg. 49
- UC 140 chicken dolly, aluminumpg. 49
- UC 200 stainless steel dolliespg. 49

ALUMINUM UTILITY CART

2 and 3 shelf units

Shelves have 3 lips-up and 1 lip-down, 5" Poly-U casters

All welded aluminum construction, 6063-aluminum alloy

Model Number	Overall Dimensions						Shelf Size	# of Shelves		Approx Ship Wt	
	Length		Depth		Height						
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)				(lb)	(kg)
UC10-3218-2	38	965	20	508	38	965	32 x 18	2		28	13
UC10-3218-3	38	965	20	508	38	965	32 x 18	3		33	15
UC10-3321-2	39	991	23	584	38	965	33 x 21	2		30	14
UC10-3321-3	39	991	23	584	38	965	33 x 21	3		35	16
UC10-4921-2	55	1397	23	584	38	965	49 x 21	2		38	17
UC10-4921-3	55	1397	23	584	38	965	49 x 21	3		43	20



Freight Class: 250



STAINLESS STEEL UTILITY CART

2 and 3 shelf units

Shelves have 3 lips-up and 1 lip-down, 5" x 2" Poly-U casters

All welded stainless construction, Type 304 stainless alloy

Model Number	Overall Dimensions						Shelf Size	# of Shelves		Approx Ship Wt	
	Length		Depth		Height						
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)				(lb)	(kg)
UC20-3218-2	38	965	20	508	38	965	32 x 18	2		76	34
UC20-3218-3	38	965	20	508	38	965	32 x 18	3		92	42
UC10-3321-2	39	991	23	584	38	965	33 x 21	2		84	38
UC20-3321-3	39	991	23	584	38	965	33 x 21	3		101	46
UC20-4921-2	55	1397	23	584	38	965	49 x 21	2		102	46
UC20-4921-3	55	1397	23	584	38	965	49 x 21	3		122	55



Freight Class: 250

OPTION

VB - Vertical Corner Bumpers



ALUMINUM TRANSPORT UTILITY CART

Channel Construction
5" Poly-U plate casters, 2 swivel, 2 rigid
All welded aluminum construction, 6063 aluminum alloy

Model Number	Overall Dimensions						Approx Ship Wt	
	Length		Depth		Height		(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)		
UC30-3620	42	1067	20	508	36	914	40	18
UC30-4420	50	1270	20	508	36	914	46	21



Freight Class: 250

OPTION
 HD - 5x2 Heavy Duty
 Poly-U Caster



STEEL TUBULAR DECK CART

5" Poly-U plate casters, 2 swivel, 2 rigid
All welded heavy duty steel construction, Powder coat finish

Model Number	Overall Dimensions						Approx Ship Wt	
	Length		Depth		Height		(lb)	(kg)
STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)		
UC40-3618	42	1067	18	457	40	1016	52	24

Freight Class: 250

OPTION
 HD - 5x2 Heavy Duty
 Poly-U Caster



PRODUCE STOCKING CART

5" Poly-U plate casters, 2 swivel, 2 rigid

All welded heavy duty steel construction, Powder coat finish

Model Number	Overall Dimensions						Approx Ship Wt	
	Length		Depth		Height		(lb)	(kg)
GALVANIZED STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)		
UC50-2244	52	1321	22	559	36	914	65	29

Freight Class: 250



WET PRODUCE STOCKING CART REVERSIBLE TOP SHELF

5" Poly-U plate casters, 2 swivel, 2 rigid

All welded heavy duty galvanized steel

Model Number	Overall Dimensions						Approx Ship Wt	
	Length		Depth		Height		(lb)	(kg)
GALVANIZED STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)		
UC60-2240	48	1219	22	559	40	1016	108	49

Freight Class: 250



QUEEN MARY CARTS

3, 4, 5, AND 6 SHELF UNITS

**Shelves have 3 lips-up and 1 lip-down with marine edge,
Available with all lips down, Tubular Shelf Reinforcement,
1-1/4" HD Tubular Construction, Full Perimeter Bumper, Handle,
8" x 2" Poly-U plate casters, 2-rigid and 2-swivel w/brakes,
All welded aluminum construction, 6063-aluminum alloy**

Model Number	Overall Dimensions						Approx Ship Wt	
	Width		Depth		Height		(lb)	(kg)
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)		
UC70-3	69	1753	28	711	70	1778	150	68
UC70-4	69	1753	28	711	70	1778	170	77
UC70-5	69	1753	28	711	70	1778	190	86
UC70-6	69	1753	28	711	70	1778	210	95



Freight Class: 250

OPTION
LD - All Lips Down



All welded stainless steel construction, Type 304 alloy

Model Number	Overall Dimensions						Approx Ship Wt	
	Width		Depth		Height		(lb)	(kg)
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)		
UC80-3	69	1753	28	711	70	1778	260	118
UC80-4	69	1753	28	711	70	1778	290	132
UC80-5	69	1753	28	711	70	1778	320	145
UC80-6	69	1753	28	711	70	1778	350	159



Freight Class: 350

OPTION
LD - All Lips Down



ALUMINUM DOLLIES

SOLID BASE

5" Poly-U plate casters, 2 swivel, 2 rigid
 HD units have 5" x 2" Poly-O casters,
 3003-H14 aluminum sheet metal

Model Number	Overall Dimensions						Approx Ship Wt	
	Width		Depth		Height			
MEAT TRAY DOLLY	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
UC100-2027	21	533	28	711	8	203	19	9



Freight Class: 150



Model Number	Overall Dimensions						Approx Ship Wt	
	Width		Depth		Height			
BOX BEEF DOLLIES	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
UC100-1826-HD	19	483	27	686	9	229	23	10
UC100-2733-HD	28	711	34	864	9	229	23	10



Freight Class: 150



ALUMINUM SHEET PAN DOLLIES

FOR 18 X 26 SHEET PANS

5" Poly-U swivel plate casters, All welded aluminum tubular construction with solid base

Model Number	Overall Dimensions						Approx Ship Wt	
	Width		Depth		Height			
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
UC130-1826	22	559	27	686	32	813	24	11
UC130-1826-2	22	559	27	686	32	813	27	12



Freight Class: 250




CHICKEN DOLLY / WET MOVER

5" Poly-U stem casters, removable drip pan
All welded aluminum construction, 6063 alloy

Model Number	Overall Dimensions						Approx Ship Wt	
	Width		Depth		Height			
ALUMINUM	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
UC140	21	533	28	711	12	305	25	11



Freight Class: 100



MILK CRATE DOLLIES

OPEN BASE

3" Poly-U plate casters • 1-1/2" angular all welded construction, Type 304 stainless alloy

Model Number	Overall Dimensions						Approx Ship Wt	
	Width		Depth		Height			
STAINLESS STEEL	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
UC200-1414	15	381	15	381	7	178	8	4
UC200-1428	15	381	29	737	7	178	10	5
UC200-1442	15	381	43	1092	7	178	12	5
UC200-2828	29	737	29	737	7	178	14	6



Freight Class: 200



