

ITEM NO.
PASS-THRU REFRIGERATED CABINET
SSRPT2-S

() REQUIRED

1. Provide two-section pass-thru refrigerated cabinet, Delfield model SSRPT2-S. Net storage capacity to be minimum 51.92 cubic feet. Provide with 6" stainless steel adjustable legs.
2. Cabinet exterior sides, front and shroud shall be 22-gauge, corrosion resistant stainless steel. Upper shroud shall be hinged, with stay-open feature to provide easy access to refrigeration system. Cabinet interior shall be 22-gauge, corrosion resistant stainless steel. Bottom and top surfaces are die stamped to provide radius corners and recessed floor.
3. Full-height solid doors (**with hinging to be determined and confirmed in writing**) Door exterior shall be 22-gauge, corrosion resistant stainless steel. Interior liner shall be resilient high impact ABS material or stainless steel, formed to protrude beyond the door gasket to protect the gasket from tearing. Each door has two edge mount, self-closing, cam lift style hinges. Doors can be removed from cabinet without the use of tools. Metal door handle is recessed into the door for easy grip without impacting aisle space. Keyed door lock is mounted in the door next to the handle. Lock engages into a heavy-duty strike mounted to the cabinet face. Door gaskets are magnetic and mount to the door snapping in place and are removable without tools.
4. Base shall be fully insulated with high-density foamed in place polyurethane.
5. Three chrome plated wire shelves are provided per section. Shelves rest on clips that are adjustable in 1" increments on stainless steel pilasters affixed to the cabinet interior. Pilasters are removable without tools for cleaning. Interior light mounted to the interior ceiling is controlled automatically through a switch mounted in the hinge assembly to protect against breakage. Door openings are protected with heavy gauge stainless steel breaker strips. An air duct is mounted to the ceiling assuring low velocity, even air movement throughout the cabinet interior.
6. Electrical connections shall be 115V, 60Hz, single phase. A 10' cord and plug is supplied attached to a junction box mounted on the exterior top of the cabinet.
7. Refrigeration system shall be top-mounted 1/3 horsepower system and shall use R404A refrigerant. All components are mounted to the exterior cabinet ceiling, outside the food zone and are assembled as one piece and can be removed as one piece. System has the capability of maintaining between 27°F and 44°F in heavy use food service operations. Refrigerant is metered using a highly responsive thermostatic expansion valve. System is controlled using ACT-Advanced Control Technology electronic temperature control, which provides improved pull down times, reducing compressor cycling and longer compressor life with lower energy consumption. Control system uses adaptive defrost to assure evaporator coil is free of ice and operating at optimum efficiency. Evaporator condensate is eliminated using an energy efficient hot gas system.
8. Provide the unit with the following accessories:

Universal Pan Slides – 12 Pair (per section).
9. Unit shall be UL and NSF approved.
10. Provide (2) year parts and labor warranty and (5) year compressor warranty.
11. Unit to be delivered, uncrated, and set in place and installed. All packing materials to be removed from job site.