



Project \_\_\_\_\_  
 Item \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 CSI Section 11400  
 Approved \_\_\_\_\_  
 Date \_\_\_\_\_

# T14D Blast Chiller/Shock Freezer

T14D: Blast Chiller/Shock Freezer

Model <b>CONVOCHILL™</b> by Delfield T14D Blast Chiller/Shock Freezer	Companion piece to the following products.		
	OES 6.20	OES 10.10	OES 10.20
	OEB 6.20	OEB 10.10	OEB 10.20
	OGS 6.20	OGS 10.10	OGS 10.20
	OGB 6.20	OGB 10.10	OGB 10.20



## Standard Features

- Blast chill cycle: 154lb. chilling capacity - from 200°F to 38° F in approximately 90 minutes
- Shock freeze cycle: 120lb. freezing capacity - from 200°F to 0°F in approximately 240 minutes
- On board, integral printer - date, temperatures and times during all chilling cycles printed out
- Automatic hot gas defrost
- Electronic control with 99 program capability and HACCP memory
- Time chill or temperature chill
- 1 core temperature probe
- Stainless steel interior and exterior
- Soft chill cycle for delicate foods
- Self-contained condensing unit
- Standard 1 year parts and labor, 5 year compressor warranty

## Options & Accessories

- Casters
- Trolley guide for use with 6.20 or 10.10 ConvoTherm rack

## Specifications

**Exterior:** Cabinet exterior sides, front, door and grill are corrosion resistant stainless steel.

**Interior:** Cabinet interior is corrosion resistant stainless steel. Bottom and side corner surfaces are stamped to provide radius corners and recessed floors. Chrome plated pan racks accommodate up to (26) 12" x 20" x 2 1/2" deep, or (13) 18" x 26" full size pans. Pan lip rests in pan slide assembly. Pan slide assembly is easily removable without the use of tools for cleaning. Stainless steel evaporator housing is mounted to the rear of the cabinet and removes for cleaning or evaporator access without the use of tools.





**Doors:** Stainless steel exterior and stainless steel interior door liner. Doors are field reversible with predrilled hinge mounting holes on both sides of the cabinet. Door seals tight to the cabinet with a magnetic door gasket. Gaskets snap into place and is easily removable without the use of tools.

**Refrigeration system:** Evaporator and condensing unit are self-contained and standard with the unit. Condensing unit is mounted at the bottom of the cabinet. The evaporator is mounted to the rear of the cabinet interior. Environmentally friendly R404A refrigerant is used. System has the capability of chilling up to 154lbs. of product from 200°F to 38°F in approximately 90 minutes or freezing up to 120lbs. of product from 200°F to 8°F in approximately 240 minutes. Two fans mounted to the front of the evaporator moves air at velocity sufficient to assure rapid, even cooling. System is controlled by an electronic microprocessor control designed for easy operation. Unit is designed to chill or freeze either for a designated time period, programmed by the user or by temperature as monitored by a probe placed in the food product. One temperature probe is supplied. Operator has the choice of using a soft chill cycle for chilling delicate product or a hard chill cycle for denser, less delicate product. Evaporator defrost is automatic using a time/temperature terminated system. User also has the option of initiating a defrost cycle manually. Evaporator condensate is eliminated using an energy efficient hot gas system.


**Electrical:** Standard electrical connections are 220-230/60/3. Connection must be hard wired to a junction box.



# T14D: Blast Chiller/Shock Freezer



Sample Printout



Model	Voltage	Comp. H.P.	Total Max Amps	Max Fuse Size	Average Heat Rejected (W)	Ship Weight
T14D	220-230/3/60	3.0	20.0	25.0	9,900	650